KO	CMC	


Specification Approval Sheet

Model: CR123A1600mAh+PTC

Prepared By/Date	Checked By/Date	Approved By/Date

Customer Approval	Confirmation	Date
Customer Approval		

Note: 1. Kindly please sign on the above and send it back to us if the sample is approved. 2. Kindly please contact us as soon as possible if the sample isn't approved. Thanks!



1. Scope

This specification is suitable for the performance of the *Lithium and Manganese Dioxide* battery.

2. Model

CR123A1600mAh+PTC

3. Reference Document

IEC60086-2: 2001 Primary batteries-Part 2: Physical and technological specifications, MOD GB 8897.2: 2005 Primary batteries-Part 2: Physical and technological specifications


4. Specification

No.	Items		Specification
1	Nominal Voltage		3.0 V
2	Capacity	Nominal	1300 mAh
	(Discharge Current 1mA to 2.0V)	Minimum	1200 mAh
3	Max. Discharge Current	Continuous	1600 mA
5		Pulse	3000 mA
4	Discharge Cut-off Voltage		2.0 V
5	Weight		Approx. 16 g
6	Operating Temperature		-40 ℃ to 60 ℃
7	Storage Temperature		-10 ℃ to 40 ℃
8	Relative humidity		6 5±20%
9	Period of Validity		10 years
10	Note:Polyswitch (PTC:144) is inside the cell.		


	Космос


5. Test Conditions and Performance





|--|





Items	Description	Dimension
D	Diameter	Max17.0mm
Т	Height	Max34.5mm

	Космос

7. Cautions in use

To ensure proper use of the battery please read the manual cafefully before using it

Hading

- A. Do not expose to ,dispose of the battery in fire.
- B. Do not put the battery in a charger or equipment with wrong terminals connected
- C. Avoid shorting the battery
- D. Avoid excessive physical shock or vibration
- E. Do not disassemble or deform the battery
- F. Do not immerse in water
- G. Do not use the battery mixed with other different make, type, or model batteries
- H. Keep out of the reach of children

Stroage

Store the battery in a cool, dry and well-ventilated area

Disposal

- A regulations vary for different countries
- B Dispose of in accordance with local regulations

8. Note

Any other items which are not covered in this specification shall be agreed by both parties