



Type Designation	4706
Designation IEC	LR6
System	Zn-MnO ₂ (Alkaline)
Shelf Life (Coding)*	10 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	2980 (discharge with high-resistance)
Permissible Temperature Range	- 20 °C ... 50 °C
Weight, approx. [g]	23,8
Volume [ccm]	7.5

Dimensions [mm]	min:	max:
Ø	13.5	14.5
A	-	50.5
B	49.2	-
C	7.0	-
E	-	0.5
F	-	5.5
G	1.0	-

Typical Capacities (at 20°C):



Discharge Type	Load	End Voltage[V]	0.9
1H/D, 7D/W	250 mA	Time [h]	9,35
CD / MD / Electronic game		Capacity [mAh]	2340
		Energy [mWh]	2771
Discharge Type	Load	End Voltage[V]	0.9
10S/M, 1H/D, 7D/W	1000 mA	Pulse [n]	610
Photo Flash		Capacity [mAh]	1698
		Energy [mWh]	1983
Discharge Type	Load	End Voltage[V]	1.05
2S/28S, 5M/H	1500 mW/650mW	Pulse [n]	120
Digital Still Camera		Capacity [mAh]	541
		Energy [mWh]	705

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.