


Data Sheet

Recommended Application: Photo

6207



| | |
|-------------------------------|---|
| Type Designation | CR V3 |
| Designation IEC | CR V3 |
| System | Li-MnO ₂ |
| Shelf Life * | 10 years |
| Nominal Voltage [V] | 3 |
| Typical Capacity C [mAh] | 3300 (Load 200 Ω at 20° C down to 1.8V) |
| Permissible Temperature Range | - 20 °C ... 70 °C |
| Weight, approx. [g] | 38 |
| Volume [ccm] | 20 |

Dimensions [mm] min: max:

| | | |
|---|------|------|
| H | 51.0 | 52.0 |
| L | 28.0 | 29.0 |
| W | 13.5 | 14.5 |

Typical Capacities (at 20 °C)

| Discharge Type | Load | End Voltage[V] | 2.0 | 1.8 |
|------------------------------------|-------|----------------|------|------|
| Pulse Test 15s/m, 7d/w | 3.9 Ω | Time [cy] | 1020 | 1065 |
| | | Capacity [Ah] | 2.75 | 2.85 |
| | | Energy [Wh] | 7.6 | 7.8 |
| Discharge Type | Load | End Voltage[V] | 2.0 | 1.8 |
| Service Output Test 24h/d, 7d/w | 200 Ω | Time [h] | 234 | 249 |
| | | Capacity [Ah] | 3.18 | 3.35 |
| | | Energy [Wh] | 9.1 | 9.4 |

* In consideration of typical loss of capacity at storage and application.