


SANYO

Cadnica

Cell Type N-1200SCK

Specifications




Dimensions of Bare Cell		H	42.0 ±0.3 mm
		1.654 ±0.012 inch	
	D	22.0 ±0.3 mm	
		0.866 ±0.012 inch	
	d	10.0 mm	
		0.394 inch	


Nominal Capacity		1200mAh	
Nominal Voltage		1.2V	
Charging Current	Standard	120mA	
	Quick	360mA	
Charging Time	Standard	14 to 16Hrs.	
	Quick	4 to 6Hrs.	
Ambient Temperature	Charge	Standard	0°C to +70°C [+32°F to 158°F]
		Quick	10°C to +70°C [+50°F to 158°F]
	Discharge		-20°C to +70°C [-4°F to 158°F]
	Storage		-30°C to +70°C [-22°F to 158°F]
Internal Impedance (Av.) (at 50% discharge)		4.2mΩ (at 1000Hz)	
Weight		52g/1.83oz	
Dimensions(D)×(H) (with t ube)		22.9 ⁰ ₋₁ × 43.0 ⁰ _{-1.2} mm	
		0.90 ⁰ _{-0.04} × 1.69 ⁰ _{-0.05} inch	

Typical Characteristics


Charge




Discharge (at high rate)




Charge



Discharge (at high rate)



Discharge (at low rate)



Temperature (Charge & Discharge)

