

# Extended capability multi chemistry charger

## EcMC<sup>2</sup> 250

Lightweight field charger  
Dependable performance

The EcMC<sup>2</sup> 250 is a state of the art two-channel, four-position charger. Easy to transport and friendly to operate, it automatically recognizes the type of military battery. Recharges batteries simultaneously, regardless of SOC or chemistry.

### Benefits

- Charges different battery types
- Charges different battery chemistries
- Fast battery charge
- Soldier portable
- Worldwide usage
- Quiet operation
- Intuitive plug-and-charge operation
- LED indication of charge status

### Key features

- Automatic battery recognition
- Charges both channels simultaneously, regardless of battery type or chemistry
- Automatic power sharing
- Conditioning charge for battery storage
- On-board HMI
- Rugged construction for a long life of field operations
- Lightweight and compact
- Wide AC input, for worldwide functionality
- Wide DC input, for charging from vehicles, fuel cells, etc...
- Input cables (AC, DC) included
- Electronic and mechanical batteries interface included

### Typical applications

- Capability to charge more than 50 military Li-ion, Ni-MH and Ni-Cd battery types
- Ideal for missions involving various battery types:
  - Peace keeping
  - Law enforcement
  - Exercise and training
  - Combat



### Electrical characteristics

AC input voltage	85 – 265 V (50-60 Hz, +/- 5%)
DC input voltage	11 – 14 V and 19 – 32 V
Output power	250 W
Charger voltage	4 – 34 V
Maximum output current	10 A (per channel)

### Physical characteristics

Length	410 mm
Width	240 mm
Height	205 mm
Weight	< 9 kg (AC, DC cables included)
Volume	20.2 litres
Environmental Protection	IP44 (open) IP67 (closed)
Operating Temperature Range	-20°C to +60°C
Storage Temperature Range	-40°C to +75°C

### References

Temperature	MIL-STD 810E 503.3
Altitude	MIL-STD 810E 500.3 II-3
Vibration	MIL-STD 810E 514.4 Cat 8
Shock	MIL-STD 810E 516.4 I
Drop	MIL-STD 810E 516.4 IV
Salt Fog	MIL-STD 810E 509.3 I
Immersion	MIL-STD 810E 512.3 II-3
NSN	6130 14 564 1779
Part number	09101F



**saft**

# EcMC<sup>2</sup> 250

## Technology features

- Microprocessor controlled
- Built-in multiple redundant safety protection
- Software field upgradeable (*future proof*)
- BIT (*Built In self Test*)
- DC input automatic cut off to prevent deep discharge of vehicle battery
- SM Bus (*smart battery*) compatible
- AC and DC input protection by field re-settable circuit breakers

## Materials

- Case: high impact polypropylene
- Colour: black
- Control panel: aluminium/ABC
- Cables: 105°C rated PVC

## Built-in protection devices ensure safety in case of:

- Exposure to heat
- Exposure to direct sunlight for extended periods
- Short circuit
- Over voltage
- Under voltage
- Transient voltage spikes

## Transportation and storage:

- For long term storage use a dry place at a temperature preferably not exceeding +50°C
- Short term storage at -40°C to +75°C is possible

## Performance characteristics for Li-ion batteries

SAI 2590	2 charged in approx. 5 hours
SAI 2800	2 charged in approx. 5 hours
SALLY	2 charged in approx. 5 hours
PR4G military battery	BA684A-AL1142-AL1146 BA685A-AL1143
Etc... (capable of charging more than 50 battery types)	

## Safety/Reliability standards

Information Technology Equipment	EN 60950-1
MTBF (MIL HDBK-217F GB)	40 000 h at 25°C
Operational ceiling	700 hPa

## EMI standards

EMC emission	EN 61000-6 3 & 4 MIL-STD 461D RE102 Ground Army
EMC immunity	EN 61000-6 1 & 2 MIL-STD 461D RS103 Ground Army
RF emission	FCC 47 CFR Ch 1, Pt 15
Mains input connector	IEC 320/C

## References

Charger unit	O9120A	NSN (To Be Advised)
Interface	GP16497	NSN (To Be Advised)
Cable DC/DC	GP16715	NSN (To Be Advised)
Cable AC/DC	GP16716	NSN (To Be Advised)

## Saft

### Specialty Battery Group

12, rue Sadi Carnot  
93170 Bagnolet – France  
Tel +33 (0)1 49 93 19 18  
Fax +33 (0)1 49 93 19 69

[www.saftbatteries.com](http://www.saftbatteries.com)

Doc. N° 32010-2-0510

Information in this document is subject to change without notice and becomes contractual only after written confirmation by Saft.

Published by the Communications Department.

Photo credit: Saft

Société anonyme au capital de 31 944 000 €  
RCS Bobigny B 383 703 873



**SAFT**